



DIN規格 L(ライト)シリーズ

ホース	ねじ	コード	品名	H	ΦA	B	C	D	L	CL		
6	M12P1.5	6404794	GXK6-04M12	17	6.2	7	12	6	44	25		
	M14P1.5	6404805	GXK8-04M14	17	8.2	7.5	11	6	43	24		
	M16P1.5	6404639	GXK10-04M16	17	10.2	7	12	6	44	25		
	M18P1.5	6426087	GXK12-04M18	19	12.2	7	12	6	44	25		
9	M14P1.5	6426099	GXK8-06M14	19	8.2	7.5	11	6	43	24		
	M16P1.5	6404641	GXK10.2-06M16	19	10.4	7	12	6	44	25		
	M18P1.5	6404642	GXK12-06M18	19	12.2	7	12	8	46	27		
	M22P1.5	6404643	GXK15-06M22	27	15.2	7.5	13	8	47	28		
12	M22P1.5	6420262	GXK15-08M22	27	15.2	7.5	13	8	58	29		
	M26P1.5	6420260	GXK18-08M26	27	18.2	8	14	8	59	30		
15	M26P1.5	6424707	GXK18-10M26	30	18.2	8	14	11	64	35		
	M30P2	6432721	GXK22-10M30P2	36	22.2	7.5	14	10	62	32		
19	M30P2	6436141	GXK22-12M30P2	36	22	8	14	10	72	34		
	M36P2	6437862	GXK28-12M36P2	41	28.2	14	18	10	76	38		
25	M36P2	6432723	GXK28-16M36P2	41	28.2	7.5	14	13	85	39		
	M45P2	6432732	GXK35-16M45P2	50	35.2	10.5	16	13	87	41		

DIN規格 S(ヘビー)シリーズ

ホース	ねじ	コード	品名	H	ΦA	B	C	D	L	CL		
6	M14P1.5	6425781	GXK6-04M14	17	6.2	7	12	6	44	25		
9	M20P1.5	6424178	GXK12-06M20	22	12.2	7	12	8	46	27		
	M22P1.5	6426848	GXK14-06M22H24	24	14	7.5	13	8	47	28		
	M22P1.5	6423541	GXK14-06M22	27	14	7.5	13	8	47	28		
12	M20P1.5	6422372	GXK12-08M20	22	12.2	7	12	10	57	28		
	M24P1.5	6420261	GXK16-08M24	27	16.2	8	14	8	59	30		
15	M30P2	6433006	GXK20-10M30P2	36	20.2	10	14	10	62	32		
19	M36P2	6434011	GXK25-12M36P2	41	25.2	12	18	10	76	38		
25	M42P2	6432353	GXK30-16M42P2	46	30.2	14	18	13	89	43		

継手金具の最高使用圧力は『付1』ページをご参照ください。