



ホース	ヘッド サイズ	品名	適応範囲						ΦB	ΦA	t	J	L	CL
			35	70	140	210	280	350						
32	16	NXI-3F-2016	○	○					44.5	39.68	8.0	65	107.0	71.0
	20	NXI-3F-2020	○	○					50.8	44.51	8.0	68	110.0	74.0
	24	NXI-3F-2024	○	○					60.3	53.84	8	30	72.0	36.0
	16	NXI-3F-212016			○	○	○		44.5	39.68	8.0	65	133.0	76.0
	20	NXI-3F-212020			○	○	○		50.8	44.51	8.0	85	153.0	96.0
	24	NXI-3F-212024			○	○	○		60.3	53.84	8	87	155.0	98.0
	20	NXI3F-055-212020			○	○	○		50.8	44.51	8	55	123.0	66.0
	20	NXI3F-120-212020			○	○	○		50.8	44.51	8	120	188.0	131.0
	16	NXGI-3F-602016						○	44.5	39.68	8.0	65	155.5	76.5
	20	NXGI-3F-602020						○	50.8	44.51	8.0	71	161.5	82.5
38	24	NXI-3F-2424	○	○					60.3	53.84	8.0	70	119.0	76.0
	32	NXI-3F-2432	○	○					71.4	63.37	9.5	50	99.0	56.0
	24	NXI-3F-402424			○	○			60.3	53.84	8.0	87	165.4	99.4
	32	NXI-3F-402432			○	○			71.4	63.37	9.5	95	173.4	107.4
	24	NXI-3F-602424					○	○	60.3	53.84	8.0	73	171.0	88.0
50	32	NXI-3F-3232	○	○					71.4	63.37	9.5	80	134.0	86.0
	40	NXI-3F-3240	○	○					84.1	76.20	9.5	50	104	56.0
	32	NXI-3F-213232			○	○			71.4	63.37	9.5	101	193.0	114.0

CL: ホース切断時に差し引く長さ(参考値)