


金具タイプ No. 906F

SAEハイプレッシャー(6000)フランジ 90° ベンド



ホース	ヘッド サイズ	品名	適応範囲						ΦB	ΦA	t	F	J	L	CL
			35	70	140	210	280	350							
32	16	NX90F-6F-212016			○	○	○		47.6	39.68	9.5	65	80	148.0	91.0
	20	NX90F-6F-212020			○	○	○		54	44.51	10.3	74	91	159.0	102.0
	24	NX90F-6F-212024			○	○	○		63.5	53.84	12.6	82	91	159.0	102.0
	16	NX906F-100-212016			○	○	○		47.6	39.68	9.5	100	82	150.0	93.0
	20	NX906F-100-212020			○	○	○		54.0	44.51	10.3	100	91	159.0	102.0
	24	NX906F-116D38-212024			○	○	○		63.5	53.84	12.6	116	96	164.0	107.0
	20	NX906F-140-212020			○	○	○		54.0	44.51	10.3	140	91	159.0	102.0
	16	NX906F-150-212016			○	○	○		47.6	39.68	9.5	150	82	150.0	93.0
	20	NX906F-150-212020			○	○	○		54.0	44.51	10.3	150	91	159.0	102.0
	20	NX906F-200-212020			○	○	○		54.0	44.51	10.3	200	91	159.0	102.0
	16	NXG90F-6F-602016						○	47.6	39.68	9.5	75	82	172.5	93.5
	20	NXG90F-6F-602020						○	54	44.51	10.3	100	96	186.5	107.5
	24	NXG90F-6F-602024						○	63.5	53.84	12.6	116	96	186.5	107.5
	16	NXG906F-100-602016						○	47.6	39.68	9.5	100	82	172.5	93.5
	20	NXG906F-110-602020						○	54.0	44.51	10.3	110	96	186.5	107.5
	20	NXG906F-120-602020						○	54.0	44.51	10.3	120	96	186.5	107.5
	20	NXG906F-130-602020						○	54.0	44.51	10.3	130	96	186.5	107.5
	20	NXG906F-150-602020						○	54.0	44.51	10.3	150	96	186.5	107.5
	20	NXG906F-160-602020						○	54.0	44.51	10.3	160	96	186.5	107.5
	20	NXG906F-170-602020						○	54.0	44.51	10.3	170	96	186.5	107.5
	16	NXG906F-180-602016						○	47.6	39.68	9.5	180	82	172.5	93.5
	20	NXG906F-180-602020						○	54.0	44.51	10.3	180	96	186.5	107.5
	20	NXG906F-210-602020						○	54.0	44.51	10.3	210	96	186.5	107.5
20	NXG906F-255-602020						○	54.0	44.51	10.3	255	96	186.5	107.5	
38	24	NX90F-6F-2424	○	○				63.5	53.84	12.6	101	117	166.0	123.0	
	32	NX90F-6F-2432	○	○				79.4	63.37	12.6	115	117	166.0	123.0	
	24	NX90F-6F-402424			○	○		63.5	53.84	12.6	116	115	193.4	127.4	
	20	NX90F-6F-602420					○	54.0	44.51	10.3	100	96	194.0	111.0	
	24	NX90F-6F-602424					○	63.5	53.84	12.6	115	115	213.0	130.0	
	32	NX90F-6F-602432					○	79.4	63.37	12.6	115	115	213.0	130.0	
	20	NX906F-120-602420					○	54.0	44.51	10.3	120	96	194.0	111.0	
	20	NX906F-150-602420					○	54.0	44.51	10.3	150	96	194.0	111.0	
	20	NX906F-215-602420					○	54.0	44.51	10.3	215	96	194.0	111.0	
	20	NX906F-250-602420					○	54.0	44.51	10.3	250	96	194.0	111.0	
	24	NX906F-250-602424					○	63.5	53.84	12.6	250	115	213.0	130.0	
50	32	NX90F-6F-213232			○	○		79.4	63.37	12.6	140	145	237.0	158.0	
	32	HDG90F-6F-603232					○	79.4	63.37	12.6	155	166	313.6	182.6	
	32	HDG906F-220-603232					○	79.4	63.37	12.6	220	166	313.6	182.6	

CL: ホース切断時に差し引く長さ(参考値)