



ホース	ねじ	コード	品名	H	A	F	J	L	CL	適用Oリング
6	9/16-18UNF	6404644	GX45KO-0409	19	8.5	21	41	65	46	AS568-011
	11/16-16UN	6432996	GX45KO-0411	22	9	22	61.5	86	56	AS568-012
9	11/16-16UN	6404645	GX45KO-0611	22	9	22	55	79	60	AS568-012
	13/16-16UN	6407171	GX45KO-0613	27	10	22	53	77	58	AS568-014
12	13/16-16UN	6420270	GX45KO-0813	27	10	22	51	86	57	AS568-014
	1-14UNS	6426362	GX45KO-0816	32	10.5	26	55	90	61	AS568-016
	1-3/16-12UN	6435565	GX45KO-0819	36	11.5	31	70	105	76	AS568-016
15	13/16-16UN	6425860	GX45KO-1013	27	10	22	51	87	58	AS568-014
	1-14UNS	6420803	GX45KO-1016	32	10.5	26	64	100	71	AS568-016
	1-14UNS	6421173	GX45KO-035-1016	32	10.5	35	73	109	80	AS568-016
	1-3/16-12UN	6421172	GX45KO-1019	36	11.5	26	64	100	71	AS568-018
	1-3/16-12UN	6426571	GX45KO-040-1019	36	11.5	40	94	130	101	AS568-018
19	13/16-16UN	6424785	GX45KO-1213	27	10	26	64	111	73	AS568-014
	1-14UNS	6426063	GX45KO-1216	32	10.5	26	64	111	73	AS568-016
	1-3/16-12UN	6420880	GX45KO-1219	36	11.5	26	64	111	73	AS568-016
	1-3/16-12UN	6426572	GX45KO-040-1219	36	11.5	40	92	139	101	AS568-016
	1-3/16-12UN	6426563	GX45KO-100-1219	36	11.5	100	138	185	147	AS568-016
	1-7/16-12UN	6428595	GX45KO-1223	41	11.5	32	70	117	79	AS568-021
25	1-3/16-12UN	6430085	GX45KO-1619	36	11.5	31.5	76	132	86	AS568-016
	1-7/16-12UN	6429215	GXC 45KO-1623	41	11.5	31.5	76	132	86	AS568-021

CL: ホース切断時に差し引く長さ(参考値)