



ホース	ねじ	コード	品名	H	ΦA	B	C	L	CL	適用Oリング
6	G1/4B	6404637	GX2R-04	19	11	11.5	6	44	24	P11
	G1/4B	6436287	GX2R-04C9	19	11	11.5	9	47	27	P11
	G3/8B	6400575	GX2R-0406	22	14	11.5	8	46	26	P14
	G1/4B	6430331	GX2R-04 SUS	19	11	11.5	6	44	24	P11
9	G1/4B	6428820	GX2R-0604	19	11	11.5	6	44	24	P11
	G3/8B	6404638	GX2R-06	22	14	11.5	6	44	24	P14
	G3/8B	6436288	GX2R-06C10	22	14	11.5	10	48	28	P14
	G3/8B	6430098	GX2R-06 SUS (210K)	22	14	11.5	6	44	24	P14
	G1/2B	6404812	GX2R-0608	27	18	15.5	8	50	30	P18
12	G1/2B	6420295	GX2R-08	27	18	15.5	8	61	32	P18
	G1/2B		GX2R-08C10 (近日発売予定)				10			P18
15	G1/2B	6425565	GX2R-1008	27	18	15.5	12	66	36	P18
	G3/4B	6421092	GX2R-1012	36	23.7	16	10.5	64	35	P24
19	G3/4B	6420885	GX2R-12	36	23.7	16	10.5	75	37	P24
	G1B	6420886	GX2R-1216	41	29	18	12	78	40	P29
25	G1B	6421071	GX2R-16	41	29	18	13	89	43	P29
	G1・1/4B	6421073	GX2R-1620	50	38	20	13	91	45	P38

CL:ホース切断時に差し引く長さ(参考値)